

SCHWEGO[®] fix 8110

Cleaner for fountain solution circulations

Function: **SCHWEGO[®] fix 8110** will clean the damping water system and kills fungi, bacteria and yeasts. Even in case of optimum filtration and conservation, germ formation will be a topic in fountain solution circulations again and again. This will lead to substantial trouble in the printing process in most cases.

Apart from the soiling of the fountain solution circulation, germs might have further negative influences, for instance on the pH-value.

The fountain solution circulation should be cleaned regularly with **SCHWEGO[®] fix 8110**, especially with IPA-free printing.

Properties:

- Intensive abatement of germs in the fountain solution circulation
- Deposits are killed and flushed out
- Regular cleaning will prevent the building up in pipes and ducts

Application: Add 2-3% **SCHWEGO[®] fix 8110** into the fountain solution circulation, filled with fresh water. Rinse the system for about 2-3 hours.

If possible, close the return unit and allow the cleaning solution to react in the total system for about 30 minutes.

Then drain the system and rinse once with clear water and once with water and 10 % fountain additive.

Tip: Use biocides safely. Always read the label and product information before use.

Subject to appropriate storage, the described properties of **SCHWEGO[®] fix 8110** remain stable for at least 18 months.

Packaging: 10 kg canister

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 05/2019