

certified by



SCHWEGO® soft 1000 W speed

Fountain additive for IPA-free sheetfed offset printing

Function	SCHWEGO® soft 1000 W speed is used for isopropyl alcohol (IPA) free/reduced sheetfed offset printing. Optimized wetting agents allow an isopropyl alcohol (IPA) addition of maximum 4 %. This quantity of addition gradually can be reduced.
Tip	Detailed information for printing without IPA is available in our flyer "Printing without alcohol".
Properties	<ul style="list-style-type: none">• Suitable for water hardness up to 12° KH• Fast free-running behaviour• Stable ink-water emulsion• Stable adjustment of the pH-value• Reduced ink build-up on the damping rollers• Used for new Generation and fast running presses• Complexing of the hardness formers will prevent any deposits on the ink and damping rollers• Suitable for UV and special inks• Checked and released according to the default settings of the leading machine builders
Quantity to add	SCHWEGO® soft 1000 W speed is added to the water with a share of about 2-4%.
Storage	Subject to appropriate storage, the described properties of SCHWEGO® soft 1000 W speed remain stable for at least 12 months.
Packaging	10 kg canister 20 kg canister 200 kg drum 1000 kg container

The above information is based on our current knowledge and experience.
No binding assurance in respect of certain properties or suitability for certain applications must be read into our information.
Patent rights and other proprietary rights must be observed if necessary.
Further safety instructions please learn from our material safety data sheet.

