

SCHWEGO® soft 1000 W speed

Fountain additive for IPA-free sheetfed offset printing

Function SCHWEGO® soft 1000 W speed is used for isopropyl alcohol (IPA) free/reduced sheetfed offset printing. Optimized wetting agents allow an isopropyl alcohol (IPA) addition of maximum 4 %. This quantity of addition gradually can be reduced.

SCHWEGO® soft 1000 W speed for water hardness up to 12° KH
SCHWEGO® soft 1000 N speed for water hardness as from 12° KH

Tip Detailed information for printing without IPA is available in our flyer "Printing without alcohol".

Properties

- Fast free-running behaviour
- Stable ink-water emulsion
- Stable adjustment of the pH-value
- Reduced ink build-up on the damping rollers
- Used for new Generation and fast running presses
- Complexing of the hardness formers will prevent any deposits on the ink and damping rollers
- Suitable for UV and special inks

Quantity to add SCHWEGO® soft 1000 W/N speed is added to the water with a share of about 2-4%

Storage Subject to appropriate storage, the described properties of SCHWEGO® soft 1000 W speed and SCHWEGO® soft 1000 N speed remain stable for at least 12 months.

Packaging 10 kg canister | 20 kg canister | 200 kg drum | 600 kg container | 1000 kg container

