

SCHWEGO[®] wett 6237

Wetting additive for water-based coating systems

Chemical base: Silicone polymers with organic solvents

Properties: **SCHWEGO[®] wett 6237** possesses a very high surface activity, which leads to improved wetting of the substrate by aqueous coating materials. In many cases **SCHWEGO[®] wett 6237** also improves the flow. **SCHWEGO[®] wett 6237** does not interfere with recoatability.

Applications: **SCHWEGO[®] wett 6237** can be used in all types of water-based systems such as:

- Dispersions
- Emulsions
- Hybrids
- Neutralisation systems

SCHWEGO[®] wett 6237 is suitable for organic and inorganic pigments.

Technical data:
(Guide values)

Appearance	: colourless clear liquid
Density (ISO 2811-1)	: 0.94 g/cm ³
Flash point (ISO 1523)	: > 100 °C
Non volatile content (ISO 3251)	: 22 %
Solvent	: glycoether

Processing: The dosage of **SCHWEGO[®] wett 6237** is 0.1 – 0.5 % (calculated on total system). It is recommended to add **SCHWEGO[®] wett 6237** at the beginning of the production. Predilution before incorporation is advisable.

Storage: Do not store **SCHWEGO[®] wett 6237** at temperatures below 0 °C and above 30° C. Stir it up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO[®] wett 6237** remain stable for at least 2 years provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.
Further safety instructions please learn from our material safety data sheet. 03/2019