

SCHWEGO® soft 1000 W / N

Multifunctional fountain additive for sheetfed offset printing

certified by



Function SCHWEGO® soft 1000 W / N are a universally applicable fountain water additives for sheetfed offset printing. SCHWEGO® soft 1000 W / N are also very suitable for hybrid technology and for printing with UV-inks.

They offer constant conditions in the printing process by its wide range of applications, even with demanding subjects and problematic substrates.

SCHWEGO® soft 1000 W for water hardness up to 10° KH
SCHWEGO® soft 1000 N for water hardness from 8° to 14° KH

Properties

- Excellent anti-linting behaviour (reduces lint build-up)
- Stable ink- water emulsion, especially with process inks and special colours
- Optimized complexing of the hardness formers prevents deposits on the ink and damping rollers
- Stable adjustment of the pH-value
- Fast free running behaviour
- Suitable for CtP-plates
- Checked and released according to the default settings of the leading machine builders

Quantity to add SCHWEGO® soft 1000 W / N are added to the water with a ratio of 2-3%.

Storage Subject to appropriate storage, the described properties of SCHWEGO® soft 1000 W / N remain stable for at least 12 months

Packaging 10 kg canister | 20 kg canister | 200 kg drum | 600 kg container | 1000 kg container

