

SCHWEGO[®] aqua solv 8480

Aqueous cleaning agent for water-based flexographic and gravure printing inks

Function: **SCHWEGO[®] aqua solv 8480** is used to clean anilox rollers, ink ducts, ink pumps, cylinders, chamber doctor blades and other machine parts. **SCHWEGO[®] aqua solv 8480** can also be used in part washing units.

SCHWEGO[®] aqua solv 8480 convinced by its wide range of applications, outstanding cleaning effect and the economically advantageous consumption.

Characteristics:

- Neutral smell
- Non-combustible
- Water-dilutable
- Tensides are biologically degradable
- Low VOC



Application: **SCHWEGO[®] aqua solv 8480** can be diluted with water up to a ratio of 1:1. The cleaning effect can be considerably improved by reaction time and higher temperatures (up to 60°C).

Tip: Certified by BG ETEM as "low emission product"

Subject to appropriate storage, the described properties of **SCHWEGO[®] aqua solv 8480** remain stable for at least 12 months.

Packaging: 20 L can / 200 L drum / 600L /1000 L container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 05/2019