

SCHWEGO® soft 1000 A eco

Fountain additive for IPA-free sheetfed offset printing, meets the criteria of various environmental labels

certified by



Function SCHWEGO® soft 1000 A is used for isopropyl alcohol (IPA) free/reduced sheetfed offset printing. Optimized wetting agents allow an isopropyl alcohol (IPA) addition of maximum 4 %. This quantity of addition gradually can be reduced.

SCHWEGO® soft 1000 AW eco for water hardness up to 12° KH
SCHWEGO® soft 1000 AN eco for water hardness as from 12° KH

For detailed information on printing without IPA, please see our flyer "Printing without Alcohol."

Properties

- meets the criteria of various environmental labels (e.g. Ecolabel, blauer Engel)
- Fast free-running behaviour
- Stable ink-water emulsion
- Stable adjustment of the pH-value
- Reduced ink build-up on the damping rollers
- Complexing of the hardness formers will prevent any deposits on the ink and damping rollers
- Suitable for UV und special inks
- Checked and released according to default settings of the machine builders

Quantity to add SCHWEGO® soft 1000 A eco is added to the water with a ratio of 2-4%.

Storage Subject to appropriate storage, the described properties of SCHWEGO® soft 1000 A eco remain stable for at least 12 months.

Packaging 10 kg canister | 20 kg canister | 200 kg drum | 1000 kg container |

