

## SCHWEGO® soft 3000 AWG eco

Fountain additive for heatset printing, meets the criteria of various environmental labels

certified by



**Function** SCHWEGO® soft 3000 AWG eco was developed for the extensive requirements and possibilities of heatset printing. This fountain additive is especially suitable for machines on which various paper grades are used. Depending on the machine configuration and technical conditions, SCHWEGO® soft 3000 AWG eco will also ensure printing without isopropyl alcohol (IPA).

### Properties

- meets the criteria of various environmental labels
- Suitable for water hardness up to 12° KH
- Convincing production printing properties especially with B-stock-paper grades
- Defined adjustment of the surface and interfacial surface tension
- Special wetting agents ensure a reduction of the water and ink flow
- Optimized emulsifying behaviour with LWC and B-stock-ink
- Excellent anti-linting behaviour (reduces lint build-up)
- Reducing of feed-back to fountain rollers
- Suitable for CTP-plates
- Stable adjustment of the pH-value
- Fast running-free behaviour
- Checked and released according to the default settings of the machine builders

**Quantity to add** SCHWEGO® soft 3000 AWG eco is added to the water with a ratio of 2-3%.

**Storage** Storage not under 5 °C.

Subject to appropriate storage, the described properties of SCHWEGO® soft 3000 AWG eco remain stable for at least 12 months.

**Packaging** 10 kg canister | 20 kg canister | 200 kg drum | 1000 kg container

