

SCHWEGO® soft 1000 WT

Fountain additive for sheetfed offset printing with drying accelerant

certified by



Function SCHWEGO® soft 1000 WT is a universally applicable fountain water additive with drying accelerant for sheetfed offset printing. SCHWEGO® soft 1000 WT is also very suitable for hybrid technology and printing with UV-inks.

A special additive will affect a faster surface drying of the printed sheets.

It offers constant conditions in the printing process by its wide range of applications, even with demanding subjects and problematic substrates.

SCHWEGO® soft 1000 WT for water hardness up to 10° KH

Properties

- Fastened surface drying of the printing ink
- Excellent anti-linting behaviour (reduces lint build-up)
- Stable ink-water emulsion, especially with process inks and special colours
- Optimized complexing of the hardness formers prevents any deposits on the ink and damping rollers
- Stable adjustment of the pH-value
- Fast free running behaviour
- Checked and released according to the default values of the leading machine builders

Quantity to add SCHWEGO® soft 1000 WT is added to the water with a ratio of 2-4%.

Storage Subject to appropriate storage, the described properties of SCHWEGO® soft 1000 WT remains stable for at least 12 months.

Packaging 10 kg canister | 20 kg canister | 200 kg drum | 600 kg container | 1000 kg container

