

## SCHWEGO<sup>®</sup> gum 8177

### Preservative for all printing plates

**Function:** **SCHWEGO<sup>®</sup> gum 8177** will protect the printing plate from oxidation and mechanical influences for a long time. The synthetic composition offers a strong and flexible protective film.

**Properties:**

- Fast film formation after the application
- Protection from oxidation
- Does not attack the printing plate
- Strong and flexible protective layer
- Long-term protection for the plate storing
- Easy removal of the protective film by means of water
- Suitable for all offset printing plates

**Application:**

In case of prolonged dead halts of the machine or for filing the printing plate, clean it with **SCHWEGO<sup>®</sup> al 8195** and then apply a thin layer of **SCHWEGO<sup>®</sup> gum 8177**.

Wash the printing plate with water before beginning to print.

When plate processors are used, we recommend a dilution of about 3:2 with water.

**Tip:**

Subject to appropriate storage, the described properties of **SCHWEGO<sup>®</sup> gum 8177** remain stable for at least 12 months.

**Packaging:**

10 kg canister

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 12/2019