

## SCHWEGO® eco wett 6215

Wetting and dispersing additive for water-based coating systems | biodegradable | free of VOC

Chemical base Polymer

Properties SCHWEGO® eco wett 6215 controls the stability of the coating system at the

pigment/binder interface. SCHWEGO® eco wett 6215 facilitates the formation of primary particles during the dispersion process and prevents reagglomeration. Thus dispersion process is improved, the colouring power is improved and hard settlement is prevented. By using SCHWEGO® eco wett 6215 the viscosity of the mill base is reduced. Therefore, it is well suitable for highly pigmented systems.

FDA approval The compounds of SCHWEGO® eco wett 6215 are listed in FDA (U.S. Food & Drug

Administration), title 21, Code of Federal Regulations (CFR). Details are visible in

our Regulatory Information Sheet.

Applications SCHWEGO® eco wett 6215 shows excellent dispersing properties, preferred

application during dispersion of organic and inorganic pigments in high solid content or systems of high PVC. SCHWEGO® eco wett 6215 is intended for use in all water-based air drying, stoving and 2K-systems. It is compatible with alkyd resins, polyester systems, epoxy esters, acrylates, styrene / acrylates and

polyurethane systems.

SCHWEGO® eco wett 6215 maintains the moisture level and can therefore also be

used as humactant (advantageous when using e.g. PEG 400).

Technical data Appearance clear to cloudy, light yellow liquid

(Guide values) Density (ISO 2811-1) 1,11 g/cm<sup>3</sup>

Flash point (ISO 1523) > 150 °C Non volatile content (ISO 3251) 100%

Processing SCHWEGO® eco wett 6215 should be added to the mill base in order to get

optimum use of its wetting properties. The quantity to be added is 0.5 – 6.0 %,

calculated on pigment.

Storage Do not store SCHWEGO® eco wett 6215 at temperatures below 0 °C and above

30° C. Stir it up before use. Keep in a cool, well-ventilated place. Subject to appropriate storage, the described properties of SCHWEGO® eco wett 6215 remain stable for at least 2 years.

provided the original container is closed after use.

Packaging 50 kg drum | 200 kg drum

