

SCHWEGO[®] foam 6388

Defoamer for solvent borne and water-based coating systems, VOC-free

Chemical base: Surface active polymers in a solvent mixture

Properties: **SCHWEGO[®] foam 6388** is an interfacially active additive, which influences the surface tension. Hence, the formation of bubbles during the manufacture of paint or during application is reduced to a minimum. Any bubbles formed are quickly destroyed. In general **SCHWEGO[®] foam 6388** has beneficial effect on the flow of the paint film.

Applications: Solvent borne and water-based coating systems, especially suitable in polyester systems.

Technical data:
(Guide values)

Appearance	:	clear, yellow liquid
Density (ISO 2811-1)	:	0.85 g/cm ³
Flash point (ISO 1523)	:	> 150 °C
Active matter	:	100 %

Processing: **SCHWEGO[®] foam 6388** must be carefully dispersed into the system. **SCHWEGO[®] foam 6388** should be added at the beginning of production. The dosage is 0.1 - 0.5 %, calculated on total formulation.

Storage: Do not store **SCHWEGO[®] foam 6388** at temperatures below 0 °C and above 30° C. Stir it up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO[®] foam 6388** remain stable for at least 2 years, provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 08/2020