

BLISTER FREE 88

Defoamer for solvent borne coating systems, biodegradable

Chemical base: Surface active polymers in a solvent mixture

Properties: **BLISTER FREE 88** is an interfacially active additive, which influences the surface tension. This property reduces the formation of bubbles to a minimum during the production of coatings or during application. Any bubbles formed are quickly destroyed. **BLISTER FREE 88** improves levelling.

FDA approval: The non-volatile compound of **BLISTER FREE 88** is listed in FDA (U. S. Food & Drug Administration), title 21, Code of Federal Regulations (CFR), part 175.300.

Applications: **BLISTER FREE 88** is especially suitable in polyester systems free from paraffins. **BLISTER FREE 88** shows also good defoaming in epoxy, PUR and acrylate based systems.

Technical data:
(Guide values)

Appearance	:	clear, colourless liquid
Density (ISO 2811-1)	:	0.88 g/cm ³
Flash point (ISO 1523)	:	44 °C
Active matter	:	100 %

Processing: The dosage is 0.1 - 0.5 %, calculated on total system. **BLISTER FREE 88** should be added at the beginning of production.

Storage: Do not store **BLISTER FREE 88** at temperatures below 5 °C and above 30°C. Stir it up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **BLISTER FREE 88** remain stable for at least 2 years, provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.
Further safety instructions please learn from our material safety data sheet. 03/2019